
INOXlook



Lindner aluminium ceilings can be ordered with INOXlook appearance on request. The surface 'INOXlook' is created by special rolling and anodizing processes and is similar to a grinded stainless steel surface (grain 180).

Technical Specifications:

- raw material: aluminium manufactured according to EN 485-4 und EN 573-3
- gauge of anodizing cover: 5 μ for 0.5 and 0.8 mm material thickness
10 μ for 1.0, 1.5 and 2.0 mm material thickness
- anodized according to EN 12373
- Surface will be equipped with a protective foil by factory.

Advantages compared to stainless steel:

- significant weight reduction allows the application of a weaker substructure
- anodization provides excellent protection against corrosion and abrasion
- protection against finger prints on the surface
- very comfortable cleaning by means of common detergents
- surface can be sterilized
- well suited for laser processing (cut-out)

Subject to change without notice. This document is intellectual property of Amstorf based Lindner-Holding KGaA. It may neither be duplicated, exploited for profit, distributed for business purposes nor shown to any third parties without our approval. Please note that all details, schemes, pictures and dimensions shown in this catalogue are without commitment and might vary due to final project requirements. Especially all figures shown in inch are rough dimensions only. Our O&M manuals, Installation Recommendations, Product Specification Sheet, etc. and the installation of Lindner products are exclusively foreseen for persons with special metal ceiling knowledge. For safety reasons all others are not allowed to use Lindner's products. Lindner ceilings must be installed as a complete system. Missing, wrong or by other products substituted components, additional loads by services for e.g. luminaries and not by Lindner approved anchors can cause failure of the complete ceiling system. Lindner ceilings are high-quality products for the interior only. All in our documents mentioned performances are subject to correct installation according to our company's manuals and Standard Terms and Conditions.